

 SmartOne Solar <i>Solar Powered Asset Manager</i>	 SmartOne C <i>Asset Manager</i>	 SPOT TRACE <i>Satellite Tracking Device</i>
KEY FEATURES	\$349.00	\$179.00	\$129.99
INTRINSICALLY SAFE	ATEX/IECEx II 1 G, Ex ia IIC T4 Ga For International Zone 0 applications, HERO Class I, Division 1, Groups A-D, T4 Class I, Zone 0, AEx ia IIC T4 Ga	×	×
HAZARDS OF ELECTROMAGNETIC RADIATION TO ORDINANCE CERTIFIED (HERO)	✓	×	×
POWER	Solar-powered with up to 10 years of battery life	Lithium batteries provides 1.5+ years of life 5V DC or 8-24V DC with regulator cable	Lithium batteries (Not Waterproof) <i>Included</i> Waterproof DC power cable. <i>Sold Separately</i>
DATA & MAPPING USER INTERFACE	SPOT My Globalstar	SPOT My Globalstar	SPOT Mapping or SPOT My Globalstar
TRACKING & REPORTING	<ul style="list-style-type: none"> • GPS Location reporting in 4 modes • Geofencing with configurable range setting • Stationary or in-motion reporting • Reduced messaging & theft recovery modes 	<ul style="list-style-type: none"> • Up to 12 different reporting times • Low battery message • On-board geofencing for immediate arrival and departure alerts • Built-in motion sensor 	<ul style="list-style-type: none"> • Customized tracking from every 2.5 to 60 min. • Alerts users when the vibration sensor detects new movement • Configuration to track an asset that is primarily stored on the water • Dock Mode • Low battery message • Daily status alert
BLUETOOTH / INPUTS / API	Bluetooth interface for configuration and firmware updating. Two dry contact or wetted-voltage inputs available to manage engine run time, capable of integration with BLE sensors or various alarm inputs.	<ul style="list-style-type: none"> • Two dry contact inputs • TTL serial communication • Power via cable at 5V DC or 8-24V DC regulated 	Power via cable at 5V DC or 8-22V DC regulated
DIMENSIONS	HEIGHT: 3.25" WIDTH: 7" THICKNESS: 1.125"	HEIGHT: 2.7" WIDTH: 3.25" (with brackets) THICKNESS: 1"	HEIGHT: 2.69" WIDTH: 2.02" THICKNESS: 0.95"
WEIGHT	13.5 oz/385 g <i>With optional mounting bracket 40.57 oz. (1150 g)</i>	3.6 oz <i>With 4 batteries and mounting hardware</i>	3.1 oz
OPERATING TEMPERATURE	-40 °C to +65 °C (-40 °F to 149 °F)	-30 °C to 60 °C (-22 °F to 140 °F)	-30 °C to 60 °C (-22 °F to 140 °F)
RATING	IP68/69K	IP67	IP67
BATTERY TYPE	Built-in rechargeable NiMH batteries (<i>non-replaceable</i>)	4 AAA Energizer Ultimate Lithium (L92) <i>Included</i> 1.5V lithium	4 AAA Energizer Ultimate Lithium (L92) <i>Included</i> 4 AAA Energizer® NiMH rechargeable batteries (NH12) <i>Sold Separately</i>
INSTALLATION	Quick and easy installation requires no harnesses, external power or external antennas	Quick and easy installation requires no external power or external antennas	Quick and easy installation requires no external power or external antennas
APPLICATIONS	Energy/Oil & Gas, Construction, Transportation/Trailers/Containers, Maritime	Construction, Transportation/Trailers/Containers	Recreation, Consumer Retail - Boats, Cargo, Personal Vehicles or Fleets, Work Tools