

	SmartOne Solar Solar Powered Asset Manager	SmartOne C Asset Manager	SPOT TRACE Satellite Tracking Device
KEY FEATURES	\$449.00	\$229.00	\$174.99
INTRINSICALLY SAFE	ATEX/IECEx for Zone 0 International North America cETLus Class I, Zone 0, AExia IIC T4 Ga Class I, Div 1, Goups A-D T4	×	×
HAZARDS OF ELECTROMAGNETIC RADIATION To ordinance certified (hero)	\checkmark	×	×
POWER	Solar-powered with up to 10 years of battery life	Operates on 5V external line power, 8-24V regulator cable, or (4) AAA Lithium batteries	Lithium batteries Line power with a 5v USB connection (Not Waterproof) Included Waterproof DC power cable. Sold Separately
DATA & MAPPING USER INTERFACE	SPOT My Globalstar	SPOT My Globalstar	SPOT Mapping or SPOT My Globalstar
TRACKING & REPORTING	 GPS Location reporting in 4 modes Geofencing with configurable range setting Stationary or in-motion reporting Reduced messaging & theft recovery modes Receives and transmits data from external sensors 	 Up to 12 different reporting times Low battery message On-board geofencing for immediate arrival and departure alerts Built-in motion sensor Built-in temperature sensor 	 Customized tracking from every 2.5 to 60 min. Alerts users when the vibration sensor detects new movement Configuration to track an asset that is primarily stored on the water Power off message notification Low battery message Daily status alert
BLUETOOTH / INPUTS / API	Bluetooth interface for configuration and firmware updating Two dry contact or wetted-voltage inputs available to manage engine run time, tank level or various alarm inputs	Local programming Interface cable Published API for VAR Integrations – data integrations	API - device data output
DIMENSIONS	HEIGHT: 8.26 cm (3.25 in) WIDTH: 17.78 cm (7 in) THICKNESS: 2.86 cm (1.125 in)	HEIGHT: 6.86 cm (2.7 in) WIDTH: 8.26 cm (3.25 in) <i>with brackets</i> THICKNESS: 2.54 cm (1 in)	HEIGHT: 6.83 cm (2.69 in) WIDTH: 5.13 cm (2.02 in) THICKNESS: 2.14 cm (0.95 in)
WEIGHT	385 g (13.5 oz) With optional mounting bracket 40.57 oz. (1150 g)	102 g (3.6 oz) With 4 batteries and mounting hardware	87.9 g (3.1 oz)
OPERATING TEMPERATURE	-40° C to 65° C (-40° F to 149° F)	-30° C to 60° C (-22° F to 140° F)	-30° C to 60° C (-22° F to 140° F)
RATING	IP68/69K	IP67	IP67
BATTERY TYPE	Built-in rechargeable NiMH batteries (non-replaceable)	4 AAA 1.5V lithium	 4 AAA Energizer Ultimate Lithium 8x batteries (L92) Included 4 AAA Energizer® NiMH rechargeable batteries (NH12) Sold Separately
INSTALLATION	Quick and easy installation requires no harnesses, external power or external antennas	Quick and easy installation requires no external power or external antennas	Quick and easy installation requires no external power or external antennas
APPLICATIONS	Energy/Oil & Gas, Construction, Transporation/Trailers/Containers, Maritime	Construction, Transporation/Trailers/Containers	Recreation, Consumer Retail - Boats, Cargo, Personal Vehicles or Fleets, Heavy Equipment, Work Tools