



# SPOT FOR BUSINESS

SPOT devices deliver affordable, reliable, location-based tracking, messaging and life-saving S.O.S. technology to hundreds of thousands of users around the world 24/7.

## SPOT GEN4™ GLOBAL SATELLITE GPS MESSENGER

### ENHANCED TRACKING SERVICES

#### CUSTOM TRACKING RATE

SPOT Gen4's customized tracking allows you to change the rate tracks are sent to 2 ½, 5, 10, 30, or 60 minutes. Extreme Tracking upgrade is required for 2 ½ minute tracking.

#### MOTION-ACTIVATED TRACKING

A vibration sensor tells SPOT to send your GPS location when you are moving and to stop when you do. This conserves battery power and avoids sending duplicate tracks.

#### CONTINUOUS TRACKING

SPOT Gen4 will send track messages until you turn off your SPOT. No need to reset after 24 hours.

### BACK OFFICE SOLUTION

**SPOT Mapping** is an enhanced mapping interface that empowers users to maximize the value of their SPOT devices. Managers can interact with all devices and operators from a single, centralized, cloud-based platform that provides live or historical tracking of personnel, vehicles, and assets on-demand.

- Live and Historical Tracking
- Reporting
- Live Alerts
- Geofencing
- Grouping

### FEATURES

#### HELP

Request help from your colleagues at your GPS location.

#### TRACK

Automatically send and save your location and allow contacts to track your progress using SPOT My Globalstar.

#### CHECK IN

Let contacts know where you are and that you're okay with a pre-programmed message.

#### CUSTOM MESSAGE

Let contacts know where you are by sending a pre-programmed message with your GPS location.

#### S.O.S.

In an emergency, send an S.O.S. with your GPS location to GEOS, who facilitates search and rescue.



SPOT GEN4

### BATTERY TYPE

- 4 AAA Energizer® Ultimate Lithium 8x batteries (L92)
- 4 AAA Energizer® NiMH rechargeable batteries (NH12)

### LONG BATTERY LIFE

Send 1,250 Check In and Custom Messages on a single set of Lithium batteries

### SPECIFICATIONS

**HEIGHT:** 3.48" (8.83 cm) **WIDTH:** 2.66" (6.76 cm)

**THICKNESS:** 0.93" (2.36 cm)

**WEIGHT:** 5 oz (142 g) with Lithium batteries

**OPERATING TEMP:** -22 F to 140 F (-30 C to 60 C)

**OPERATING ALTITUDE:** -328 ft to +21,320 ft (-100 m to +6,500 m)

**HUMIDITY RATED:** MIL-STD 810F, Temperature cycling from 20°C to 60°C while maintaining 95% RH.

**VIBRATION RATED:** Per SAE J1455

**DUST AND WATER RESISTANT:** IP68

To learn more about **SPOT Gen4**, visit [eu.Globalstar.com](http://eu.Globalstar.com)