



SmartOne B/LP

Satellite-Managed Asset-Ready Tracker

Designed for the intelligent management of powered and non-powered fixed and mobile assets, the SmartOne B/LP (line-powered) is a practical solution for tracking asset location, reporting unauthorized movement, engine runtime reporting and major fault monitoring as well as a multitude of other applications. Track intermediate bulk containers, vehicles and boats as a solution to improve your assets operating efficiency and security.

The SmartOne B/LP can be line-powered (operates on external power) or in the absence, interruption or failure of line-power, the SmartOne B/LP will automatically switch to battery back-up to ensure transmissions continue. When using line-power, the user has maximum flexibility in messaging frequency allowing for regular monitoring of asset location.

The SmartOne B/LP utilizes motion sensors, comparative GPS positions and custom configured sensors to gather and transmit asset status information. Each SmartOne B/LP is configured to track its asset's specific needs and provide intermediate and emergency alerts by email or text (VAR software integration required).



FEATURES

- Quick installation: Use industrial adhesives, brackets or screw mounts for installation
- Simple packaging: Requires no harnesses, external power or external antenna
- Automatic alerts: Change of location sensing sends alerts if asset moves outside of pre-determined range
- Messaging cost reduction mode: Reduced satellite messaging if asset remains in same location for a pre-determined period of time
- Hardware on/off feature: Allows the unit to initiate GPS re-centering functionality
- Accepts serial signals (TTL) from external inputs

CONFIGURATION SOFTWARE

- Software configuration tool easily installs on PCs

BENEFITS

- Operates on external line power from 10 to 48 volts DC
- "Asset-ready" design: Allows for easy installation and field management without the need for antennas or external power
- Standard Messaging includes: Wake, GPS locate, transmit location, resume sleep and additional 12 programmable sleep and time-of-wake settings
- Messaging Cost Reduction Feature: Reduces satellite messaging if asset remains in same location or cannot obtain a GPS fix (indoors)

SMARTONE B/LP SETUP INCLUDES

- Up to 12 different reporting times
- Interval or 24 hour operation mode
- Alternate reporting scheduling
- Low battery message
- Motion Sensor/Vibration parameter and scheduling
- Contact closure parameters
- Diagnostic messages

Visit Globalstar.com/Simplex for coverage details.



SmartOne B/LP

Satellite-Managed Asset-Ready Tracker

TECHNICAL SPECIFICATIONS



OPERATING SPECIFICATIONS

DIMENSIONS	3.25 IN (H) X 6.5 IN (W) X 1.0 IN (D)	CERTIFICATIONS	- UL913 and CSA C22.2 No. 157 Certified Intrinsically Safe for use in Class I, Division 1 Groups A, B, C, D environments for US and Canada - ANATEL Certification for Brazil (pending) - FCC CFR Parts 15 and 25 - Industry Canada - CE Mark (European Certification) - COFETEL
WEIGHT	13.5 oz/385 g (with 4 batteries and mounting hardware)	STANDARDS	- SAE J1455 MIL STD 810 - NEMA 4X / IP68 - RoHS Compliant
OPERATING TEMPERATURE	-30° to +60° C NOTE: The unit shall remain operational over the -40° to +85°C range, though may experience battery life and RF signal degradation	SATELLITE TECHNOLOGY	Global LEO Satellite operation using the Globalstar Simplex Data Network
LINE POWER	Up to 48 volts DC		
BATTERY TYPE	(4) AA 1.5V lithium Provides 3+ years of battery life Removes the need to purchase expensive proprietary batteries for replacement		

ACCESSORIES

- USB Configuration Cable
- Combined Serial, LP, I/O Cable

FEATURE SET

STANDARD MESSAGING

- Wake, GPS locate, transmit location, resume sleep
- Up to 12 programmable sleep time-of-wake settings

INTEGRATED VIBRATION SENSOR

- Message on start and stop
- Engage interval override on motion for set time or while in motion
- Integrated Motion (Vibration) Sensor sends messages on start and stop motion event

ALTERNATIVE REPORTING

- Alternate supervisory reporting schedule triggered by alarm or motion
- Transmits GPS location on alternate interval for programmed time or while alarm remains active

SERIAL COMMUNICATION CAPABILITY

- User defined messages
- Serial (TTL) I/O capability to interface with remote passive and smart sensors and deliver user defined messages

MESSAGING COST REDUCTION

- Reduced satellite messaging if asset remains in same location or cannot obtain a GPS fix (indoors)

CHANGE OF LOCATION

- Theft recovery reporting based on distance moved
- Reduced messaging mode

Visit Globalstar.com/Simplex for coverage details.